

# County Surveyor's Record, Douglas County, Oregon 18491

Subdivision of Section 4,  
T. 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which new bearing trees</p> <p style="padding-left: 40px;">A hemlock, 15 ins. diam., bears N. 57° E., 16 lks. dist., mkd. C<math>\frac{1}{4}</math> S4 BT.</p> <p style="padding-left: 40px;">A cedar, 11 ins. diam., bears S. 11° E., 9 lks. dist., mkd. C<math>\frac{1}{4}</math> S4 BT.</p> <p>Depost a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2° 39' 00" W., beginning new measurement.</p> <p>Descend over broken NW. slope.</p>
1.55	Hinkle Creek, 45 lks. wide, course N. 70° W.; asc. over broken SW. slope.
13.075	Point for the center N 1/16 sec. cor. of sec. 4.
	Set a stainless steel post, 28 ins. long 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>C N 1/16   S 4 C 1987</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 16<math>\frac{1}{4}</math>° E., 4<math>\frac{1}{2}</math> lks. dist., mkd. CN 1/16 S4 BT.</p> <p style="padding-left: 40px;">A hemlock, 15 ins. diam., bears S. 69° W., 14 lks. dist., mkd. CN 1/16 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over broken SW. slope.</p>
25.385	The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 4.</p> <p>S. 86° 07' 00" W., on the E. and W. center line of sec. 4.</p> <p>Descend over SW. slope, through heavy timber and dense undergrowth.</p>
0.50	Ravine, drains S. 20° E.; asc. over NE. slope.
2.10	Spur, slopes S. 30° E.; desc. over SW. slope.
3.30	Ravine, drains S. 25° E.; asc. over SE. slope.
5.50	Spur, slopes S. 40° E.; desc. over broken SW. slope.
13.45	Hinkle Creek, 35 lks. wide, course N. 50° W.; continue over creek bottom.
20.10	Hinkle Creek, 35 lks. wide, course N. 65° W.; asc. over NE. slope.
21.655	Point for the center E 1/16 sec. cor. of sec. 4.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.