

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 4,  
T 25 S., R. 3 W., Willamette Meridian, Oregon

18495

CHAINS

E 1/16  
C S 4 C  
1987

from which

A fir, 25 ins. diam., bears N. 61½° E., 24 lks. dist.,  
mkd. CE 1/16 S4 BT.

cedar, 13 ins. diam., bears S. 22° W., 5½ lks. dist.,  
mkd. CE 1/16 S4 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the  
stainless steel post.

Ascend over NE. slope.

36.65 Spur, slopes N. 10° E.; desc. over NW. slope.

43.310 The center ¼ sec. cor. of sec. 4.

\_\_\_\_\_

S. 86° 12' 00" W., beginning new measurement.

Descend over NW. slope.

6.55 Hinkle Creek, 45 lks. wide, course S. 70° W.; continue over creek  
bottom.

20.40 Hinkle Creek, 30 lks wide, course N. 40° W.; continue over creek  
bottom.

21.35 Hinkle Creek, 40 lks. wide, course S.; asc. over broken SE. slope.

39.65 Spur, slopes S. 20° E.; desc. over SW. slope.

42.750 The ¼ sec. cor. of secs. 4 and 5, monumented with an iron post, 1  
in.diam., firmly set, projecting 12 ins. above ground, with  
brass cap mkd.

¼  
S 5 | S 4  
1944

from which the remains of bearing trees mkd. by Arthur Boyer,  
Deputy County Surveyor, in 1940

A fir stump, 28 ins. diam., bears S. 28° E., 19 lks.  
dist., with healed blaze.

A fir stump, 30 ins. diam., bears N. 43½° W., 36 lks.  
dist., with scribe marks ¼ S5 T25S R3W CS BT visible  
on opened blaze.

and the remains of a bearing tree mkd. by Price

A cedar stump, 24 ins. diam., bears N. 14¼° W., 51 lks.  
dist., with scribe marks ¼ S B visible on partially  
healed blaze.

and bearing trees mkd. by Vernon R. Tracy, Deputy County  
Surveyor, in 1966

A grand fir, 10 ins. diam., bears S. 13 3/4° E., 43 lks.  
dist., with healed double blaze.

A cedar, 13 ins. diam., bears S. 43¼° W., 24 lks.  
dist., with healed blaze.

From this point, the Douglas County horizontal control station  
"HINKLE", bears N. 56° 09' 30" W., 115.690 chs. dist., monumented