

County Surveyor's Record, Douglas County, Oregon

18496

Subdivision of Section 4,
T 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	with a brass cap, 3 ins. diam., set in a 10 in. diam., concrete filled bell tile, 3 ins. above ground, with top mkd. DOUGLAS CO SURVEYORS OFFICE HINKLE 1975.
	From the center E 1/16 sec. cor. of sec. 4.
	N. 7° 00' 00" W., on the N. and S. center line of the NE¼ of sec. 4.
	Descend over NE. slope, through heavy timber and dense undergrowth.
1.55	Hinkle Creek, 35 lks. wide, course NW.; asc. over SW. slope. changing to broken SE. slope.
12.640	Point for the NE 1/16 sec. cor. of sec. 4, at intersection with the E. and W. center line of the NE¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NE 1/16 S 4 1987
	from which
	A fir, 12 ins. diam., bears N. 20° E., 21 lks. dist., mkd. NE 1/16 S4 BT.
	A fir, 16 ins. diam., bears S. 3° E., 15½ lks. dist., mkd. NE 1/16 S4 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Ascend over SE. slope.
24.445	The E 1/16 sec. cor. of secs. 4 and 33.
	From the N 1/16 sec. cor. of secs. 3 and 4.
	S. 87° 21' 00" W., on the E. and W. center line of the NE¼ of sec. 4.
	Descend over SW. slope, through heavy timber and dense undergrowth.
9.65	Beaty Creek, 5 lks. wide, course S. 20° E.; asc. over broken SE. slope.
20.685	The NE 1/16 sec. cor. of sec. 4.
	Ascend over broken SE. slope.
27.90	Spur, slopes S. 20° E.; desc. over SW. slope.
41.370	The center N 1/16 sec. cor. of sec. 4.
	Subdivision of Section 9, T. 25 S., R 3 W., Willamette Meridian, Oregon
	From the ¼ sec. cor. of secs. 9 and 16.
	N. 1° 32' 00" W., on the N. and S. center line of sec. 9.