

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 9,  
T. 25 S., R. 3 W., Willamette Meridian, Oregon

18499

CHAINS	
90.990	<p>A fir, 31 ins. diam., bears N. 55° E., 26 lks. dist., mkd. CW 1/16 S9 BT.</p> <p>A hemlock, 6 ins. diam., bears S. 20° W., 8½ lks. dist., mkd. CW 1/16 S9 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over broken NW. slope.</p> <p>The ¼ sec. cor. of secs. 8 and 9.</p>
7.95	<p>From the W 1/16 sec. cor. of secs. 9 and 16.</p> <p>N. 1° 29' 00" W., on the N. and S. center line of the SW¼ of sec. 9.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p> <p>Spur, slopes W.; desc. over NW. slope.</p>
20.100	<p>Point for the SW. 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the SW¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 9 1987</p> <p>from which</p> <p style="text-align: center;">(see the following page for continuation of these notes)</p>