

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 9,  
T. 25 S., R. 3 W., Willamette Meridian, Oregon

18590

CHAINS	
	<p>A cedar, 9 ins. diam., bears S. 78½° E., 8 lks. dist., mkd. SW 1/16 S9 BT.</p> <p>A fir, 18 ins. diam., bears N. 22½° W., 11½ lks. dist., mkd. SW 1/16 S9 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over NW. slope.</p>
32.65	Gravelled road, 20 lks. wide, bears N. 80° E. and S. 80° W.
40.200	The center W 1/16 sec. cor. of sec. 9.
	<p>From the center S 1/16 sec. cor. of sec. 9.</p> <p>S. 87° 28' 00" W., on the E. and W. center line of the SW¼ of sec. 9.</p> <p>Ascend over NE. slope, through heavy timber and dense undergrowth.</p>
0.85	Spur, slopes N. 20° E.; desc. over NW. slope.
2.10	Creek, 1 lk. wide, course N. 35° E.; asc. over E. slope.
9.40	Spur, slopes N.; desc. over NW. slope.
22.490	The SW 1/16 sec. cor. of sec. 9.
	Descend over broken NW. slope.
44.980	The S 1/16 sec. cor. of secs. 8 and 9.
	<p>Subdivision of Section 32, T. 25 S., R. 3 W., Willamette Meridian, Oregon</p>
	<p>From the ¼ sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp. N. 2° 52' 00" E., on the N. and S. center line of sec. 32.</p> <p>Ascend over broken SW. slope, through scattered timber and open pasture.</p>
6.30	Gravelled road, 15 lks. wide, bears N. 40° W. and S. 40° E.
31.90	Spur, slopes N. 50° E.; desc. over NW. slope.
37.35	Gravelled road, 15 lks. wide, bears N. 70° E. and S. 70° W.
41.630	Point for the center ¼ sec. cor. of sec. 32, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T 25 S R 3 W C¼ S 32 1988</p>
	from which
	<p>A black oak, 15 ins. diam., bears N. 56° E., 368 lks. dist., mkd. C¼ S32 BT.</p> <p>A black oak, 10 ins. diam. bears N. 30¼° W., 493 lks. dist., mkd. C¼ S32 BT.</p>