

County Surveyor's Record, Douglas County, Oregon

18591

Subdivision of Section 32,
T 25 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located in an open pasture.</p> <p>From this point, the United States Coast and Geodetic Survey triangulation station "SCOTT ECC," 1938, bears N. 28° 00' 55" E., 126.104 chs. dist., monumented with a brass cap, 3½ ins. diam., cemented in rock, with cap mkd. U S COAST AND GEODETIC SURVEY SCOTT ECC 1938 and a triangle.</p> <p>Descend over NW. slope.</p>
44.35	Ravine, drains S. 65° W.; asc. over SE. slope.
62.70	Spur, slopes S. 35° W.; desc. over NW. slope.
66.690	<p>Point for the center N 1/16 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins long, 2½ ins. diam. 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> C N 1/16 S 32 C 1988 </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 39° W., 80 lks. dist., mkd. CN 1/16 S32 BT.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 30° W., 57½ lks. dist. mkd. CN 1/16 S32 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over NW. slope.</p>
75.30	Creek, 3 lks. wide, course SW.; asc. over SE. slope.
88.60	Gravelled road, 20 lks. wide, bears S. 35° E. and N. 30° W.
91.750	The ¼ sec. cor. of secs. 29 and 32.
	<p>From the ¼ sec. cor. of secs. 32 and 33.</p> <p>N. 84° 10' 00" W., on the E. and W. center line of Sec. 32.</p> <p>Descend over broken SW. slope, through heavy timber and dense undergrowth.</p>
2.50	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
13.20	Creek, 4 lks. wide, course S. 30° W.; asc. over broken SE. slope.
19.740	<p>Point for the center E 1/16 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> C $\frac{E\ 1/16}{S\ 32}$ C 1988 </div> <p>from which</p> <p style="margin-left: 40px;">A cedar, 24 ins. diam., bears N. 34° E., 72 lks. dist., mkd. CE 1/16 S32 BT.</p>