

# County Surveyor's Record, Douglas County, Oregon

## 18597

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

(Restoring the survey by Nathaniel Ford in 1854,  
the survey by Dennis Hathorn in 1857, the survey  
by William H. Byars in 1881, the survey and retracement  
by William F. Briggs in 1899, and the resurvey  
by Lynn M. Roseberry and James E. Jelley in 1967-77)

Beginning at the cor. of secs. 16, 17, 20, 21, monumented with  
an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above  
ground (alongside is an iron pipe, 1½ ins. diam., firmly set,  
projecting 4 ins. above ground), with brass cap mkd.

FO. OK 8/93  
B. SHAWER R.M. 377

T 29 S R 4 W			
S 17   S 16			
S 20   S 21			
1969			

from which a bearing tree mkd. by W. H. Wood, Deputy County  
Surveyor, in 1925

A fir, 31 ins. diam., bears S. 66½° E., 33½ lks. dist.,  
with healed blaze.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor,  
in 1963

A white oak, 10 ins. diam., bears N. 33° E., 57 lks.  
dist., with healed blaze. (Record, N. 34½° E., 58 lks.)

A ponderosa pine, 14 ins. diam., bears S. 49½° W.,  
61 lks. dist., with healed blaze.

A cedar, 23 ins. diam., bears N. 48 3/4° W., 85 lks. dist.,  
with healed blaze.

N. 1° 40' 00" E., on the E. bdy. of sec. 17.

Ascend over SW. slope, through scattering timber and light  
undergrowth.

3.85 Ridge, bears N. 55° W. and S. 55° E.; desc. over NE. slope.

12.00 Ravine, drains NE.; asc. over broken SE. slope.

21.950 Point for the S 1/16 sec. cor. of sec. 17 only.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

S 1/16	
S 17	
1987	

from which

A cedar, 5 ins. diam., bears S. 64° W., 15½ lks. dist.,  
mkd. S 1/16 S17 BT.

A fir, 18 ins. diam., bears N. 38° W., 60 lks. dist.,  
mkd. S 1/16 S17 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel  
post.

From this point, a point established by person(s) unknown, bears  
S. 15° 13' 00" W., 0.620 chs. dist., monumented with an iron pin,  
1 in. square, firmly set, projecting 8 ins. above ground.

From this same point, a fence corner, bears S. 14° W., 0.67 chs.  
dist., fence bears N., S., and W.