

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines **18508**
T.29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>Corner is located in an open pasture.</p> <p>Ascend over broken SE. slope.</p>
41.40	<p>Spur, slopes S. 35° E.; desc. over NE. slope.</p>
42.420	<p>The ¼ sec. cor. of secs. 16 and 17, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1958, from evidence no longer in existence, further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Markham:</p> <p style="margin-left: 40px;">A cedar, 9 ins. diam., bears S. 6½° E., 52 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears N. 44½° W., 16 lks. dist., with healed double blaze.</p> <p style="margin-left: 40px;">and a bearing tree mkd. by Byron</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears N. 31½° E., 9 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 29 S R 4 W <i>FO. OK 8/93</i></p> <p style="margin-left: 40px;">¼ <i>D. SHAWER R.M. 3-79</i></p> <p style="margin-left: 40px;">S 17 S 16</p> <p style="margin-left: 40px;">1987</p> </div> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 28'00" W., beginning new measurement.</p> <p>Descend over NE. slope.</p>
2.80	<p>Ravine, drains S. 60° E.; asc. over steep SE. slope.</p>
7.20	<p>Spur, slopes S. 70° E., desc. over steep NE. slope.</p>
20.95	<p>Creek, 6 lks. wide, course S. 30° E.; asc. over SW. slope.</p>
32.10	<p>Spur, slopes SW.; desc. over NE. slope.</p>
33.470	<p>The cor. of secs. 9 and 16 only, monumented with an iron post 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 29 S R 4 W</p> <p style="margin-left: 40px;">S 17 S 9</p> <p style="margin-left: 40px;"> S 16</p> <p style="margin-left: 40px;">1969</p> </div> <p>from which the remains of bearing trees mkd. by W. H. Wood, Deputy County Surveyor, in 1925</p> <p style="margin-left: 40px;">A fir, 19 ins. diam., bears S. 43° E., 43 lks. dist., with healed blaze. (Record, 44 lks.)</p> <p style="margin-left: 40px;">A fir, 29 ins. diam., bears S. 9° W., 35½ lks. dist., with healed blaze. (Record, 36 lks.)</p> <p style="margin-left: 40px;">A sawed fir stump, 16 ins. diam., bears N. 48½° W., 25 lks. dist., no marks visible. (Reocrd, 28 lks.)</p>