

County Surveyor's Record, Douglas County, Oregon

18599

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

and bearing trees mkd. by John H. Markham, Jr., Registered Engineer No. 2880, in 1957

A madrone, 25 ins. diam., bears S.85° E., 27 lks. dist., with fragmentary scribe marks visible on a partially healed blaze. (Record, 37 lks.)

A madrone, 30 ins. diam., bears S. 13¼° W., 138 lks. dist., with fragmentary scribe marks visible on a partially healed blaze.

and the remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963

A fir snag, 17 ins. diam., bears N. 4¼° E., 144 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

and a bearing tree mkd. by Roderick B. Kimberling, Deputy County Surveyor, in 1978

A fir, 11 ins. diam., bears N. 36¼° E., 16½ lks. dist., with healed double blaze.

N. 7° 15' 00" E., beginning new measurement

Descend over NE. slope.

5.240

The closing corner of secs. 8 and 17, on the W. bdy. of sec. 9 monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

	T 29 S R 4 W					
CC	<table style="border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">S 9</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;"></td> </tr> </table>	S 8	S 9	S 17		
S 8	S 9					
S 17						
	1969					

from which a remaining original bearing tree

A fir, 30 ins. diam., bears S. 29 3/4° W., 32 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by John H. Markham, Jr., Registered Engineer No. 2880, in 1957

A sawed fir stump, 17 ins. diam., bears N. 28 3/4° E., 80 lks. dist., no marks visible.

A sawed madrone stump, size indeterminate, bears N. 47 3/4° E., 156 lks. dist., with scribe marks visible on partially healed blaze. (Record, 159 lks.)

A madrone stump, 37 ins. diam., bears S. 42¼° E., 81 lks. dist., no marks visible.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963

A fir, 27 ins. diam., bears S. 12 3/4° W., 70 lks. dist., with healed blaze.

and a bearing tree mkd. by Roderick B. Kimberling, Deputy County Surveyor, in 1978

A fir, 11 ins. diam., bears N. 5 3/4° W., 7½ lks. dist. with healed double blaze.

From this point a control point at latitude 43° 03' 13.74" N. and longitude 123° 11' 28.98" W., established in conjunction with