

County Surveyor's Record, Douglas County, Oregon

18510

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

this survey, bears S. 50° 19' 00" W., 15.450 chs. dist., monumented with a finned aluminum rod, 36 ins. long, 3/4 in. diam., firmly set 36 ins. in the ground, in a collar of concrete, with aluminum cap mkd. EC 1 G 1394 1987.

From this same point, the 1/4 sec. cor. of secs. 8 and 17, bears N. 88° 28' 00" W., 30.400 chs. dist., hereinafter described.

From the cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground (with an iron pipe, 1 in. diam., firmly set alongside, projecting 4 ins. above ground), with brass cap mkd.

T 29 S R 4 W
S 19 | S 20
S 30 | S 29
1969

from which the remains of bearing trees mkd. by N. E. Richardson, Deputy County Surveyor, in 1945

A fir, 34 ins. diam., bears N. 34° E., 10 lks. dist., with scribe marks S 20 CS visible on the bark.

A fir, 27 ins. diam., bears S. 51° E., 50 lks. dist., with fragmentary scribe marks visible on the bark.

A sawed fir stump, 18 ins. diam., bears S. 74 1/2° W., 30 lks. dist., with scribe marks BT visible on the bark.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1963

A madrone, 16 ins. diam., bears S. 12° E., 57 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

A fir, 13 ins. diam., bears S. 19° W., 44 lks. dist., with healed blaze.

A fir, 14 ins. diam., bears N. 82° W., 12 lks. dist., with healed blaze.

N. 88° 47' 00" W., bet. secs. 19 and 30.

Descend over broken SW. slope, through heavy timber and dense undergrowth.

19.15 South Myrtle County Road No. 18, tarred surface, 25 lks. wide, bears S. 15° E. and N. 15° W.

36.30 Gravel road, 20 lks. wide, bears N. and S.

38.650 Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 29 S R 4 W
1/4 S 19
S 30
1987

from which

A ponderosa pine, 29 ins. diam., bears S. 87 1/4° E., 110 lks. dist., mkd. 1/4 S30 BT.