

County Surveyor's Record, Douglas County, Oregon

18511 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS																						
	<p style="text-align: center;">A white oak, 12 ins. diam., bears N. 42¼° W., 96 lks. dist., mkd. 1/4 S19 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Corner is located in a pasture, S. of a woven wire fence 11½ lks. dist., which bears E. and W.</p> <p>Descend over rolling, open pasture.</p>																					
66.25	South Fork Myrtle Creek, 80 lks. wide, course N. 10° W.; asc. over E. slope.																					
69.85	Ridge, bears N. and S.; desc. over W. slope.																					
73.55	South Fork Myrtle Creek, 155 lks. wide, course S. 15° W.; asc. over SE. slope.																					
76.520	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp. determined at record distance from the remaining bearing trees mkd. by Zirpel:</p> <p style="padding-left: 40px;">A cottonwood, 20 ins. diam., bears S. 53 3/4° W., 223 lks. dist., with healed blaze. (Record S. 43 3/4° W.)</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears N. 23° W., 143 lks. dist., with healed blaze. (Record, N. 21° W.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 5px;">T</td><td style="padding: 0 5px;">29</td><td style="padding: 0 5px;">S</td></tr> <tr><td style="padding: 0 5px;">R</td><td style="padding: 0 5px;">5</td><td style="padding: 0 5px;">W</td></tr> <tr><td style="padding: 0 5px;">R</td><td style="padding: 0 5px;">4</td><td style="padding: 0 5px;">W</td></tr> <tr style="border-top: 1px solid black;"><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;">24</td><td style="padding: 0 5px;">S</td></tr> <tr style="border-top: 1px solid black;"><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;">25</td><td style="padding: 0 5px;">S</td></tr> <tr style="border-top: 1px solid black;"><td style="padding: 0 5px;"></td><td style="padding: 0 5px;"></td><td style="padding: 0 5px;">30</td></tr> <tr><td style="padding: 0 5px;"></td><td style="padding: 0 5px;">1987</td><td style="padding: 0 5px;"></td></tr> </table> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A maple, 22 ins. diam., bears N. 5 3/4° E., 201 lks. dist., mkd. T29S R4W S19 BT.</p> <p style="padding-left: 40px;">A maple, 14 ins. diam., bears S. 26° E., 179 lks. dist., mkd. T29S R4W S30 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Corner is located on the N. bank of South Myrtle Creek.</p>	T	29	S	R	5	W	R	4	W	S	24	S	S	25	S			30		1987	
T	29	S																				
R	5	W																				
R	4	W																				
S	24	S																				
S	25	S																				
		30																				
	1987																					
29.20	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0° 57' 00" E., bet. secs. 19 and 20.</p> <p>Ascend over broken SW. slope, through heavy timber and dense undergrowth.</p> <p>Dirt road, 15 lks. wide, bears S. 15° E., and N. 15° W.</p>																					
39.335	<p>Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>																					