

County Surveyor's Record, Douglas County, Oregon

18512

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>T 29 S R 4 W $\frac{1}{4}$ S 19 S 20 1987</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 59° E., 48½ lks. dist., mkd. 1/4 S20 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 68° W., 18 lks. dist., mkd. 1/4 S19 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SW. slope, changing to SE. slope.</p>
78.670	<p>The cor. of secs. 19 and 20 only, on the S. bdy. of sec. 18, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1954, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1½ ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 29 S R 4 W S 18 <hr style="width: 50%; margin: auto;"/> S 19 S 20</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A rotted oak stump, 15 ins. diam., bears N. 44° W., 25 lks. dist., no marks visible. (Record, N. 45° W.)</p> <p>and a bearing tree mkd. by Irving</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 40° W., 51 lks. dist., with healed double blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 69° E., 47 lks. dist., with healed double blaze.</p>
	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89° 39' 00" W., on the N. bdy. of sec. 20.</p> <p>Descend over SW. slope, through scattering timber and light undergrowth.</p>
9.00	Power transmission lines, bear S. 25° E. and N. 25° W.
10.15	Dirt road, 20 lks. wide, bears S. 55° E. and N. 55° W.
10.70	Power transmission lines, bear S. 25° E. and N. 25° W.
11.30	Creek, 3 lks. wide, course S. 70° E.; asc. over NE. slope.
11.85	Power transmission lines, bear S. 25° E. and N. 25° W.
14.470	<p>Point for the E 1/16 sec. cor. of sec. 17 only.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 S 17 1987</p>