

County Surveyor's Record, Douglas County, Oregon

18513 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. $46\frac{1}{2}^\circ$ E., $10\frac{1}{2}$ lks. dist., mkd. E 1/16 S17 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. $7\frac{3}{4}^\circ$ W., 38 lks. dist., mkd. E 1/16 S17 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over E. slope.</p>
19.80	Tarred road, 25 lks. wide, bears S. 5° E. and N. 5° W.
32.690	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 17 only.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 4 W <u> </u> <u> </u> S 17 1987</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 58° E., $19\frac{1}{2}$ lks. dist., mkd. 1/4 S17 BT.</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. $72\frac{1}{4}^\circ$ W., $12\frac{1}{2}$ lks. dist., mkd. X BT.</p> <p>Deposit white "DEEP-1" magnetic marked at base of stainless steel post.</p> <p>Ascend over E. slope.</p>
33.330	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 4 W <u> </u> <u> </u> S 20 1987</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 57° E., 17 lks. dist., mkd. 1/4 S20 BT.</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. $55\frac{1}{2}^\circ$ W., 60 lks. dist., mkd. 1/4 S20 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken E. slope.</p>
44.10	Ridge, bears S. 30° E. and N. 30° W.; desc. over SW. slope.
53.35	Ravine, drains S. 15° E.; asc. over SE. slope.
64.30	Ridge, bears S 25° W. and N. 5° E.; desc. over SW. slope.
69.130	True point for the closing cor. of secs. 17 and 18, hereinafter described.