

# County Surveyor's Record, Douglas County, Oregon

18515

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S , R 4 W., Willamette Meridian, Oregon

**CHAINS**

77.170

The cor of secs 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T 29 S  
R 5 W R 4 W  
S 13 | S 18  
S 24 | S 19  
1957

from which the remains of bearing trees mkd. by Zirpel

A fir, 15 ins. diam., bears N. 58½° E., 153½ lks. dist., with healed blaze.

A fir, 16 ins. diam., bears S. 11½° E., 39 lks. dist., with healed blaze.

A root hole, bears S. 63° W., 92 lks. dist., with a maple, 9 ins. diam., lying alongside, no marks visible. (Record, 90 lks.)

A root hole, bears N. 3° W., 78 lks. dist., with a tipped out fir stump, 14 ins. diam., lying alongside, no marks visible. (Record, 82 lks.)

and new bearing trees

A fir, 11 ins. diam., bears S. 45° W., 68 lks. dist., mkd. T29S R5W S24 BT.

A fir, 15 ins. diam., bears N. 7½° W., 103 lks. dist., mkd. T29S R5W S13 BT.

From this point, a point established as the cor. of secs. 13, 18, 19, and 24, and recorded by John H. Markham, Jr., Registered Engineer No. 2880, bears North, 0.060 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 18 ins. above ground, from which bearing trees mkd. by Markham:

A sawed fir stump, 20 ins. diam., bears N. 20½° E., 15½ lks. dist., no marks visible.

A sawed fir stump, 21 ins. diam., bears S. 62° E., 32 lks. dist., no marks visible.

A fir, 18 ins. diam., bears S. 22½° W., 44 lks. dist., with healed double blaze.

From the ¼ sec. cor. of secs. 17 and 18, determined from the remains of a bearing tree mkd. by Briggs:

A fir stump, 12 ins. diam., bears S. 65° W., 33 lks. dist., with scribe marks 1/4 S18 B visible on opened double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T 29 S R 4 W  
¼  
S 18 | S 17  
1987

from which new bearing trees

A fir, 7 ins. diam., bears S. 15° E., 23 lks. dist., mkd. 1/4 S17 BT.