

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines **18516**  
 T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A fir, 17 ins. diam., bears N. <math>39\frac{1}{2}^\circ</math> W., 40 lks. dist.,                      mkd. 1/4 S18 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established at proportionate position as the <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 18, and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1957, and perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1970, bears N. <math>45^\circ 31' 00''</math> E., 0.080 chs. dist., monumented with an iron threaded bolt, <math>\frac{3}{4}</math> in. diam., firmly set, projecting 8 ins. above ground, from which bearing trees mkd. by Markham:</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. <math>43\frac{1}{4}^\circ</math> W., 39 lks. dist.,                      with healed blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. <math>76^\circ</math> W., 43 lks. dist.,                      with healed blaze.</p> <p style="padding-left: 40px;">and a bearing tree mkd. by Powell</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. <math>52\frac{1}{4}^\circ</math> E., 14 lks. dist.,                      with healed double blaze.</p> <p style="padding-left: 40px;">S. <math>0^\circ 36' 00''</math> W., bet. secs. 17 and 18.</p> <p>Ascend over broken NW. slope, through young timber and dense undergrowth.</p>
38.05	Ridge, bears S. $85^\circ$ E. and S. $70^\circ$ W., desc. over SW. slope.
39.10	Gravel road, 25 lks. wide, bears S. $55^\circ$ E. and N. $55^\circ$ W.
41.270	<p>The original closing cor. of secs. 17 and 18, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1954, monumented with an iron post, <math>1\frac{1}{4}</math> ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T29S R4W S18 S17, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A sawed fir stump, 22 ins. diam., bears N. <math>66\frac{1}{4}^\circ</math> W.,                      30 lks. dist., with partially healed blaze.                      (Record, N. <math>68^\circ</math> W., 33 lks.)</p> <p>and the remains of bearing trees mkd. by Irving</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. <math>42\frac{1}{2}^\circ</math> E., 33 lks. dist.,                      with healed double blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 12 ins. diam., bears N. <math>55^\circ</math> W.,                      76 lks. dist., with scribe marks BT visible on                      bark and healed blaze.</p> <p>Descend over SW. slope.</p>
41.290	<p>True point for the closing cor. of secs. 17 and 18, at intersection with the N. bdy. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 29 S R 4 W</p> <p>  C C</p> <p>  S 18   S 17</p> <p>      S 20</p> <p>      1987</p> </div> <p>from which</p>