

County Surveyor's Record, Douglas County, Oregon

18517 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS						
	<p>A fir, 15 ins. diam., bears N. 73° W., 54½ lks. dist., mkd. T29S R4W CC S18 BT.</p> <p>A fir, 18 ins. diam., bears N. 15° E., 55 lks. dist., mkd. T29S R4W CC S17 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the cor. of secs. 19 and 20 only, bears N. 89° 39' 00" W., 3.060 chs. dist., hereinbefore described.</p>					
	<p>From the ¼ sec. cor. of secs. 8 and 17, perpetuated and recorded by Arthur Boyer, Deputy County Surveyor, in 1934, from original evidence no longer in existence, and further perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1954, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p style="font-size: small;">FD OK 12/94 GI DELAN M 121-29</p> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="text-align: center;">¼ S</td></tr> <tr><td style="text-align: center;">8</td></tr> <tr><td style="text-align: center;">17</td></tr> <tr><td style="text-align: center;">T 29 S R 4 W</td></tr> <tr><td style="text-align: center;">1954</td></tr> </table> </div> <p>from which the remains of bearing trees mkd. by Boyer</p> <p style="margin-left: 40px;">A ponderosa pine, 39 ins. diam., bears S. 49° E., 46 lks. dist., with scribe marks CS BT visible on partially healed double blaze.</p> <p style="margin-left: 40px;">A sawed fir stump, 45 ins. diam., bears N. 10° W., 42 lks. dist., no marks visible.</p> <p>and a bearing tree mkd. by Irving</p> <p style="margin-left: 40px;">A cedar, 25 ins. diam., bears N. 41¼° W., 61 lks. dist., with healed double blaze.</p> <p>N. 89° 54' 00" W., bet. secs. 8 and 17.</p> <p>Descend over NW. slope, changing to broken W. slope, through heavy timber and dense undergrowth.</p>	¼ S	8	17	T 29 S R 4 W	1954
¼ S						
8						
17						
T 29 S R 4 W						
1954						
6.50	Power transmission lines, bear S. 5° E. and N. 5° W.					
14.660	Point for the NE. cor. of Donation Land Claim No. 41, hereinafter described.					
18.10	Power transmission lines, bear S. 25° E. and N. 25° W.					
18.90	Power transmission lines, bear S. 25° E. and N. 25° W.					
36.75	North Fork Myrtle Creek, 60 lks. wide, course S. 10° E.; asc. over E. slope.					
39.090	<p>True point for the cor. of secs. 7, 8, 17, and 18, located on the right bank of the North Fork Myrtle Creek, where it is impractical to set a monument, determined from the witness corner established by Ben B. Irving, Deputy County Surveyor, in 1954, hereinafter described. There is no remaining evidence of the original corner, therefore, this position is accepted as the corner.</p> <p>From this point, the ¼ sec. cor. of secs. 7 and 8, bears N. 0° 18' 00" W., 40.920 chs. dist., perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1953, from original evidence no longer in existence, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963,</p>					