

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, **18518**  
T. 29 S., R. 4 W., Willamette Meridian, Oregon

| CHAINS |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | <p>monumented with an iron post, 1½ ins. diam., firmly set, projecting 5 ins. above ground, with rotated brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE<br/> <span style="display: inline-block; text-align: center;">½ COR<br/> <u>SEC 7</u><br/>                     SEC 8</span> <span style="float: right; margin-left: 20px;"><i>FD. OK 12/94 BY DOLAN<br/>M 121-29</i></span></p> <p>From which the remains of a bearing tree mkd. by Irving</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 14° E., 64 lks. dist., with healed blaze.</p> <p>from which the remains of a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A cedar, 25 ins. diam., bears N. 18° W., 72 lks. dist., with healed blaze.</p> <p>Corner is located on NE. slope, 4 lks. W. of a woven wire fence, extending N. and S.</p>                                                                                                                                                                                                                                                                                                                                |
|        | <p>West, bet. secs. 7 and 18.</p> <p>Ascend over E. slope, through scattering timber and light undergrowth.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| 0.182  | <p>The witness cor. to the cor. of secs. 7, 8, 17 and 18, established and recorded by Ben B. Irving, Deputy County Surveyor, in 1954, monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> <span style="display: inline-block; text-align: center;">W COR<br/>                     7   8    12 FT<br/> <u>18   17</u> EAST<br/>                     T 29 S   R 4 W<br/>                     1954</span> <span style="float: right; margin-left: 20px;"><i>FD. OK 12/94 BY DOLAN<br/>M 121-29</i></span> </p> <p>from which the bearing trees mkd. by Irving</p> <p style="padding-left: 40px;">A cedar, 32 ins. diam., bears N. 38¼° E., 50 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A cedar, 20 ins. dia., bears S. 58 ¾° W. 56 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. 88¾° W. 5 lks. dist., with scribe marks BT visible on the bark.</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N. 3° W., 141 lks. dist., with healed double blaze.</p> |
|        | <p style="text-align: center;">N. 89° 53' 00" W., beginning new measurement.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 8.20   | <p>North Myrtle County Road NO. 15, tarred surface, 30 lks. wide, bears N. and S. 15° W.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 14.70  | <p>Spur, slopes S. 40° E.; desc. over SW. slope.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| 16.75  | <p>Ravine, drains S. 35° E.; asc. over NE. slope.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 19.898 | <p>Point for the E 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |