

County Surveyor's Record, Douglas County, Oregon

18519 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W, Willamette Meridian, Oregon

CHAINS

E 1/16 $\frac{S\ 7}{S\ 18}$
1988

from which

A fir, 12 ins. diam., bears S. $15\frac{1}{2}^\circ$ E., $6\frac{1}{2}$ lks. dist.,
mkd. E 1/16 S18 BT.

A fir, 23 ins. diam., bears N. $32\frac{1}{4}^\circ$ W., 75 lks. dist.,
mkd. E 1/16 S7 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel
post.

From this point, a point established by person(s) unknown, bears
N. $88^\circ 26' 00''$ E., 0.180 chs. dist., monumented with an iron
pipe, 1 in. diam., firmly set, projecting 9 ins. above ground.

Ascend over E. slope.

25.75 Ridge, bears S. 40° E. and N. 10° W.; desc. over SW. slope.

31.25 Ravine, drains S.; asc. over SE. slope.

37.05 Spur, slopes S.; desc. over SW. slope.

39.978 The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, perpetuated and recorded by
James W. Byron, Deputy County Surveyor, in 1963, monumented with
an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above
ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

$\frac{1}{4}$ S

7

18

1954

T 29 S R 4 W

from which the remains of an original bearing tree

A madrone root crown, 36 ins. diam., bears N. 7° E.,
34 lks. dist., no marks visible.

and bearing trees mkd. by Byron

A fir, 18 ins. diam., bears N. 43° E., 43 lks. dist.,
with healed blaze.

A madrone, 10 ins. diam., bears S. $54\frac{1}{2}^\circ$ E., 140 lks. dist.,
with healed blaze.

Dependent Resurvey of a Portion of the Boundaries of
Donation Land Claim No. 41,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

(Restoring the survey by Dennis Hathorn in 1857,
and the retracement by William F. Briggs in 1899)

From the true point for the cor. of secs. 7, 8, 17, and 18.

S. $89^\circ 54' 00''$ E., on the N. bdy. of Claim No. 41, identical with
line bet. secs. 8 and 17.

2.35 North Fork Myrtle Creek, 60 lks. wide, course S. 10° E.; asc.
over W. slope.