

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 17,
18521 T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	From the $\frac{1}{4}$ sec. cor. of sec. 17 only, on the S. bdy. of the section.
	N. 2° 20' 00" E., on the N. and S. center line of sec. 17.
	Ascend over SE. slope, through heavy timber and dense undergrowth.
2.20	Spur, slopes N. 85° E.; desc. over NE. slope.
17.20	Gravel road, 30 lks. wide, bears S. 50° E. and N. 55° W.
18.60	Ravine, drains N. 85° E.; asc. over SE. slope.
21.690	Point for the center S. 1/16 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	C S 1/16 S 17 C 1987
	from which
	A white fir, 10 ins. diam., bears N. 20 3/4° E., 60½ lks. dist., mkd. CS 1/16 S17 BT.
	A cedar, 12 ins. diam., bears N. 41° W., 76 lks. dist., mkd. CS 1/16 S17 BT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over SE. slope.
29.50	Gravel road, 20 lks. wide, bears N. 10° E. and S. 10° W.
40.80	Gravel road, 30 lks. wide, bears N. 50° E. and S. 50° W.
41.890	Point for the center $\frac{1}{4}$ sec. cor. of sec. 17, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 29 S R 4 W C $\frac{1}{4}$ S 17 1987
	from which
	A fir, 9 ins. diam., bears S. 41° W., 89 lks. dist., mkd. C 1/4 S 17 BT.
	A cedar, 5 ins. diam., bears N. 89 3/4° W., 89 lks. dist., mkd. C 1/4 S 17 BT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over SE. slope.
42.75	Power transmission lines, bear S. 25° E. and N. 25° W.
44.50	Power transmission lines, bear S. 25° E. and N. 25° W.