

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 17,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

18522

CHAINS	
45.50	Power transmission lines, bear S. 25° E. and N. 25° W.
50.40	Ridge, bears N. 65° E. and S. 65° W.; desc. over NW. slope
66.50	Ravine, drains N. 80° W.; asc. over SW. slope.
80.05	Spur, slopes S. 60° W.; desc. over NW slope.
81.760	The ¼ sec. cor. of secs. 8 and 17.
	From the ¼ sec. cor. of secs. 16 and 17.
	S. 89° 20' 00" W., on the E. and W. center line of sec. 17.
	Ascend over SE. slope, through heavy timber and light undergrowth.
0.75	Spur, slopes S. 35° E.; continue ascent over broken SE slope.
12.680	Point for the center E 1/16 sec. cor. of sec. 17.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$C \frac{E \ 1/16}{S \ 17} C$ 1987
	A fir, 8 ins. diam., bears S. 89½° W., 25½ lks. dist., mkd. CE 1/16 S 17 BT,
	A fir, 29 ins. diam., bears N. 9½° W., 44 lks. dist., mkd. CE 1/16 S 17 BT
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over SE. slope.
19.50	Spur, slopes S. 35° W.; desc. over W. slope.
25.55	Gravel road, 20 lks. wide, bears N. 30° E. and S. 40° W.
27.45	Same road, 25 lks. wide, bears S. 25° E. and N. 60° W.
29.45	Bottom of descent, drains S. 25° E., and also intersection of gravel roads, 45 lks. wide, bears N. 70° E., SW., and NW.; asc. over SE. slope.
30.40	Power transmission lines, bear S. 25° E. and N. 25° W.
30.95	Power transmission lines, bear S. 25° E. and N. 25° W.
31.05	Gravel road, 25 lks. wide, bears N. 65° E. and S. 50° W.
31.80	Power transmission lines, bears S. 25° E. and N. 25° W.
32.210	The center ¼ sec. cor. of sec. 17.
	Ascend over SE. slope.
41.60	Ridge, bears N. 25° E. and S. 50° W.; desc. over NW. slope.
44.890	The SE. cor. of Donation Land Claim No. 41, hereinbefore described.