

County Surveyor's Record, Douglas County, Oregon

18523

Subdivision of Section 17,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
25.010	<p>S. 89° 30' 00" W., beginning new measurement.</p> <p>Descend over broken W. slope.</p> <p>The ¼ sec. cor. of secs. 17 and 18.</p>
2.90	<p>From the E 1/16 sec. cor. of sec. 17 only, on the S. bdy. of the section.</p> <p>N. 4° 04' 00" E., on the N. and S. center line of the SE¼ of sec. 17.</p> <p>Descend over NE. slope, through scattering timber and light undergrowth.</p> <p>Creek, 5 lks. wide, course S. 30° E.; asc. over SW. slope.</p>
5.05	Power transmission lines, bear S. 25° E. and N. 25° W.
7.20	Power transmission lines, bear S. 25° E. and N. 25° W.
9.80	Power transmission lines, bear S. 25° E. and N. 25° W.
21.880	<p>Point for the SE 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the SE¼ of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 17 1987</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 49½° E., 30 lks. dist., mkd. SE 1/16 S 17 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 2¼° W., 12 lks. dist., mkd. SE 1/16 S 17 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SE. slope.</p>
42.290	<p>The center E 1/16 sec. cor. of sec. 17.</p>
13.540	<p>From the S 1/16 sec. cor. of sec. 17 only, on the E. bdy. of the section.</p> <p>S. 89° 51' 00" W., on the E. and W. center line of the SE¼ of sec. 17.</p> <p>Ascend over SE. slope, through heavy timber and light undergrowth.</p> <p>The SE 1/16 sec. cor. of sec. 17.</p> <p>Ascend over SE. slope.</p>
14.30	Spur, slopes S.; desc. over SW. slope.
20.10	Power transmission lines, bear S. 25° E. and N. 25° W.
21.20	Power transmission lines, bear S. 25° E. and N. 25° W.
22.25	Power transmission lines, bear S. 25° E. and N. 25° W.