

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 17,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

18521

CHAINS	
29.10	Creek, 4 lks. wide, course S. 30° E.; asc. over NE. slope.
32.440	The center S 1/16 sec. cor. of sec. 17.
<p>Subdivision of Section 19, T. 29 S., R. 4 W., Willamette Meridian, Oregon</p>	
	From the 1/4 sec. cor. of secs. 19 and 30.
	N. 1° 57' 00" E., on the N. and S. center line of sec. 19.
	Ascend over SW. slope, through heavy timber and light undergrowth.
6.30	South Myrtle County Road No. 18, tarred surface, 25 lks. wide, bears S. 60° E. and N. 60° W.
17.15	Spur, slopes N. 80° W.; desc. over NW. slope.
24.35	Creek, 3 lks. wide, course S. 55° W.; asc. over SE. slope.
39.160	The center 1/4 sec. cor. of sec. 19, established and recorded by William J. Ruppert, Registered Land Surveyor No. 866, in 1976, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 9 ins. above ground.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron rod, with brass cap mkd
	<p>T 29 S R 4 W C 1/4 S 19 1987</p>
	from which
	A fir, 4 ins. diam., bears S. 67 3/4° E., 13 1/2 lks. dist., mkd. X BT.
	A fir, 6 ins. diam., bears S. 15° W., 28 lks. dist., mkd. C 1/4 S 19 BT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	<hr style="width: 20%; margin: 10px auto;"/>
	N. 2° 14' 00" E., beginning new measurement.
	Ascend over S. slope, through heavy timber and dense undergrowth.
12.40	Dirt road, 15 lks. wide, bears N. 70° E. and SW.
12.45	Ridge, bears N. 60° E. and S. 40° W.; desc. over NW. slope.
25.80	Ravine, drains S. 50° W.; asc. over SE. slope.
33.70	Spur, slopes S. 35° W.; desc. over NW. slope.
39.310	The 1/4 sec. cor. of sec. 19 only, on the N. bdy. of the section.
	From the 1/4 sec. cor. of secs. 19 and 20.
	N. 89° 03' 00" W., on the E. and W. center line of sec. 19.