

County Surveyor's Record, Douglas County, Oregon

18529 Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

(Restoring the 1855 survey by Dennis Hathorn and
the 1924 resurvey by Fred Mensch)

Beginning at the cor. of secs. 19 and 30 only, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 29 S
S 19
S 30
R 7 W
1924

from which the remains of the original bearing trees

A root hole, bears N. 32° E., 38 lks. dist., with down pine alongside, 12 ins. diam., with scribe marks T29S R7W S19 BT visible on partially healed blaze.

A cedar snag, 10 ins. diam., bears S. 55° E., 20 lks. dist., with healed blaze.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1962

A cedar, 22 ins. diam., bears S. 36° E., 44 lks. dist., with healed double blaze.

and a bearing tree mkd. by Howard H. Johnstone, Registered Land Surveyor No. 498, in 1963

A cedar, 20 ins. diam., bears N. 51½° E., 47 lks. dist., with scribe marks S BT visible on partially healed blaze.

N. 0° 46' 30" E., on the W. bdy. of sec. 19.

Ascend over broken SE slope, through heavy timber and medium undergrowth.

3.90 Ridge, bears NE. and SW.; desc. over broken NW. slope.

8.040 The ¼ sec. cor. of sec. 24 only, T. 29 S., R. 8 W., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

¼
S 24
1924

from which the remains of the original bearing trees

A madrone stump, 24 ins. diam., bears S. 81° E., 20 lks. dist., no visible marks.

A madrone snag, 18 ins. diam., bears N. 12° W., 30 lks. dist., no visible marks.

and bearing trees mkd. by Mensch

A fir, 32 ins. diam., bears S. 5° W., 37 lks. dist., with healed blaze.

A fir, 19 ins. diam., bears N. 69° W., 32 lks. dist., with healed blaze.

N. 0° 05' 00" E., beginning new measurement.

Continue over NW. slope.

11.070 Point for the S 1/16 sec. cor. of sec. 19 only.