

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary, 18530  
 T 29 S , R 7 W , Willamette Meridian, Oregon

**CHAINS**

Set a stainless steel post, 28 ins long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd

| S 1/16  
 | S 19  
 1988

from which

A fir, 8 ins. diam., bears S. 85 3/4° E., 66 lks. dist., mkd. S 1/16 S19 BT.

A fir, 16 ins. diam., bears N. 82° W., 25 lks. dist., mkd. X BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

30.180

The ¼ sec. cor. of sec.19 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd

| ¼  
 | S 19  
 1924

from which a bearing tree mkd. by Mensch

A madrone, 28 ins. diam., bears S. 39° E., 78 lks. dist., with healed blaze.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1962

A madrone, 16 ins. diam., bears N. 87½° E., 10½ lks. dist., with scribe marks S19 CS visible on partially healed blaze.

From the cor. of secs. 7 and 18 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

| T 29 S  
 | S 7  
 | S 18  
 | R 7 W  
 1924

from which the remains of the original bearing trees

An oak stump, 20 ins. diam., bears N. 39° E., 8 lks dist., no marks remaining

An oak snag, 19 ins diam, bears S 55° E, 38 lks. dist., no marks remaining.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1962

A fir, 27 ins. diam., bears N. 49° E., 27 lks. dist., with healed blaze.

and a new bearing tree

A cedar, 16 ins. diam., bears S. 35¼ E., 44½ lks. dist., mkd. T29S R7W S18 BT.