County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary, T. 29 S., R. 7 W., Willamette Meridian, Oregon **18532**

CHAINS

24.80 Abandoned dirt road, 20 lks wide, bears N. 80° W., and S. 80°E.

24.960 The ¼ sec. cor. of sec. 7 only, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

¼
S 7
1924

from which bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1960

An oak, 20 ins. diam., bears N. 13° E., 60 lks. dist., with healed blaze

A madrone, 10 ins. diam, bears S. 22° E., 111 lks. dist, with healed blaze.

From this point, the witness point established by Mensch in 1924, at the Ford position for the ¼ sec. cor. of secs. 7 and 12, bears N. 82° 46' 00" W., 1.940 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.

WP
1924

from which the remains of an original bearing tree

An oak stump, 24 ins. diam., bears N. 16° E., 39 lks. dist., no marks remaining. (Record, 38 lks.)

and the remains of a bearing tree mkd. by Mensch

A fir stump, 18 ins. diam., bears N. 65° E., 34 lks. dist., with scribe marks BT visible on rotted blaze.

and the remains of bearing trees mkd.by James W. Byron, Deputy County Surveyor, in 1960

A fir, 18 ins. diam., bears S. 28° W., 60 lks. dist., with healed blaze.

A fir stump, 8 ins. diam., bears S. 42° W., 47 lks. dist., no marks visible.

and a new bearing tree

A fir, 9 ins. diam., bears N. 7° E., 22 lks. dist., mkd. X at breast height and BT at the base.

Dependent Resurvey of A Portion of the Subdivisional Lines, T. 29 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Nathaniel Ford, in 1854, and the resurvey by Fred Mensch, in 1924)

From the cor. of secs. 19, 20, 29, 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above ground with brass cap mkd.

T 29 S R 7 W
S 19 | S 20
S 30 | S 29
1924