

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, 18534
T. 29 S. R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 15 ins. diam., bears S. 26° W., 26½ lks. dist., with scribe marks S30 CS BT visible on partially healed blaze.

and a new bearing tree

A fir, 12 ins. diam., bears S. 72½° W., 10½ lks. dist., mkd. ½ S30 BT.

N. 80° 25' 30" W., beginning new measurement.

Ascend over broken SE. slope.

20.380 The W 1/16 sec. cor. of secs. 19 and 30, identical with Angle Point No. 1 of Tract 53, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

W 1/16
S 19

AP 1 | S 30
TR 53
1924

from which an original bearing tree

A fir, 9 ins. diam., bears S. 71° W., 26 lks. dist., with healed blaze. (Record, 25 lks.)

and a new bearing tree

A fir, 11 ins. diam., bears S. 34¼° E., 80½ lks. dist., mkd. W 1/16 S30 BT.

N. 80° 31' 30" W., beginning new measurement.

Continue over broken SE. slope.

21.210 The cor. of secs. 19 and 30 only, on the W. bdy. of the Tp.

From the cor. of secs. 19, 20, 29, and 30.

N. 0° 07' 30" E., bet. secs. 19 and 20.

Descend over steep NE. slope, through heavy timber and moderate undergrowth.

19.215 Point for the S 1/16 sec. cor. of secs. 19 and 20.

Set a stainless steel post, 28 ins. long. 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

S 1/16
S 19 | S 20

1988

C.S. 63/153 For NEW B.T.

from which

A fir, 13 ins. diam., bears N. 4½° E., 54 lks. dist., mkd. S 1/16 S20 BT.

A fir, 28 ins. diam., bears S. 14° W., 67½ lks. dist., mkd. S 1/16 S19 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.