

County Surveyor's Record, Douglas County, Oregon

18535

, Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
25.70	Slope changes to gradual NE. slope.
33.335	Point for Cor. No. 2 of the Oro Grande placerclaim, hereinafter described.
34.50	Dirt road, 20 lks. wide, bears N. 40° E. and S. 40° W.
37.30	Coarse Gold Creek, 10 lks. wide, course N. 35° E.; over nearly level bottom land.
37.880	Point for Cor. No. 1 (east center end corner) of the Oro Grande placer claim, hereinafter described.
38.430	The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	$\frac{1}{4}$ S 19 S 20 1924
	from which the remains of an original bearing tree
	A rotted fir stump, 18 ins. diam., bears S. 68° W., 6 lks. dist., with weathered face.
	and the remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1962
	A fir snag, 13 ins. diam., bears N. 17 $\frac{1}{2}$ ° W., 51 $\frac{1}{2}$ lks. dist., with scribe marks S19 CS BT visible on partially healed double blaze.
	and a bearing tree mkd. by Gary L. Langlitz, Deputy County Surveyor, in 1977
	A cedar, 21 ins. diam., bears N. 20 $\frac{1}{4}$ ° W., 54 lks. dist., with scribe marks $\frac{1}{4}$ C BT visible on partially healed double blaze.
	and a new bearing tree
	A fir, 11 ins. diam., bears S. 78 $\frac{1}{2}$ ° E., 93 lks. dist., mkd. $\frac{1}{4}$ S20 BT.
	From this point, the Douglas County Surveyors Office triangulation station "OLALLA", bears S. 66° 57' 10" E., 67.103 chs. dist., monumented with a concrete filled belltile, 4 ins. diam., firmly set, projecting 2 ins. above ground, with brass disk, 3 ins. diam., seated in the top, mkd. DOUGLAS COUNTY SURVEYORS OFFICE OLALLA 1976, and a triangle.
	<hr style="width: 30%; margin: 0 auto;"/> N. 1° 17' 00" E., beginning new measurement.
	Ascend over broken SE. slope.
3.995	Point for Cor. No. 6 of the Oro Grande placerclaim, hereinafter described.
9.720	Point for the S-N 1/64 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	S-N 1/64 S 19 S 20 1988