

County Surveyor's Record, Douglas County, Oregon

18537

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R.7 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A fir, 21 ins. diam., bears N. 65° W., 75 lks. dist., with healed blaze.</p> <p style="text-align: center;">and a new bearing tree</p> <p style="text-align: center;">A fir, 11 ins. diam., bears S. 48½° E., 68 lks. dist., mkd. T29S R7W S20 BT.</p>
	<p style="text-align: center;">N. 89° 23' 30" W., bet. secs. 18 and 19.</p> <p>Ascend over broken NE. slope, through heavy timber and moderate undergrowth.</p>
17.40	<p>Spur, slopes N.; desc. over NW. slope.</p>
19.160	<p>Point for the E 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S } 18}{\text{S } 19} \\ 1988 \end{array}$ </div> <p>from which</p> <p style="text-align: center;">A fir, 22 ins. diam., bears N. 35° E., 22 lks. dist., mkd. E 1/16 S18 BT.</p> <p style="text-align: center;">A madrone, 19 ins. diam., bears S. 72° W., 11 lks. dist., mkd. E 1/16 S19 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
19.20	<p>Leave timber, edge bears N. and W.; continue along N. edge of timber.</p>
38.320	<p>The ¼ sec. cor. of secs. 18 and 19, monumented with an iron post 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} \frac{1}{4} \quad \frac{\text{S } 18}{\text{S } 19} \\ 1924 \end{array}$ </div> <p>from which the remains of the bearing trees mkd. by Mensch</p> <p style="text-align: center;">A chinquapin, 20 ins. diam., bears N. 54° E., 49 lks. dist., with healed blaze. (Record, N. 53° E.)</p> <p style="text-align: center;">A root hole, bears S. 21° E., 14 lks. dist., with a down madrone alongside, 13 ins. diam., with healed blaze.</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1962</p> <p style="text-align: center;">A fir, 14 ins. diam., bears N. 89½° W., 32 lks. dist., with healed blaze.</p>
	<p>From the ¼ sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} \frac{1}{4} \quad \frac{\text{S } 7}{\text{S } 18} \\ 1924 \end{array}$ </div>