

# County Surveyor's Record, Douglas County, Oregon

## 18539

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	N. 76° 01' 00" W., beginning new measurement.  Continue over SW. slope
0.20	Ravine, drains S. 50° W.; asc. over SE. slope.
13.00	Spur, slopes S.; desc. over broken SW. slope.
22.810	The cor. of secs. 7 and 18 only, on the W. bdy. of the Tp.
<p>Subdivision of Section 7, T. 29 S., R. 7 W., Willamette Meridian, Oregon</p>	
	From the ¼ sec. cor. of secs. 7 and 18.  N. 0° 53' 00" W., on the N. and S. center line of sec. 7.  Descend over NE. slope, through heavy timber and dense undergrowth.
3.60	Ravine, drains E.; asc. over SE. slope.
7.40	Spur, slopes E.; desc. over NE. slope.
22.030	The center S 1/16 sec. cor. of sec. 7, established by Glen L. Baughman, Registered Land Surveyor No. 536, in 1973, and is accepted as the corner; monumented with a steel rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Baughman:  <div style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 70° E., 2½ lks. dist., with healed blaze.</div> <div style="margin-left: 40px;">A fir, 12 ins. diam., bears S. 27° W., 11 lks. dist., with healed blaze.</div> At the corner point  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                         C                          S 1/16   S 7                          C                          1988                     </div> Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post and the steel rod alongside.
	N. 0° 55' 00" W., beginning new measurement.  Continue over NE. slope.
5.80	Creek, 3 lks. wide, course N. 50° E.; asc. over broken SE. slope.
22.060	The center ¼ sec. cor. of sec. 7, established by Glen L. Baughman, Registered Land Surveyor No. 536, in 1973, and is accepted as the corner; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.  <div style="text-align: center;">                         T 29 S   R 7 W   SEC 7                          C   ¼                          OLS 536                     </div>