

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7,
T. 29 S., R. 7 W., Willamette Meridian, Oregon 18540

CHAINS

from which bearing trees mkd. by Baughman

A fir, 11 ins. diam., bears N. $38\frac{1}{2}^\circ$ E., 18 lks. dist.,
with healed blaze.

A fir, 11 ins. diam., bears S. 46° E., 30 lks. dist.,
with healed blaze.

From this point, a point established by N. E. Richardson,
Registered Land Surveyor No. 35, in 1947, bears S. $86^\circ 30'$ W.,
0.26 chs. dist., monumented with an iron post, 1 in. diam., with
a 2 in. angle iron welded to the side, firmly set, projecting 2
ins. above ground, from which a bearing tree mkd. by Richardson:

A cedar, 36 ins. diam., bears S. 87° W., 45 lks. dist.,
with healed blaze.

Subsequent private surveys after 1947 found this point to be
erroneously set and didn't accept it.

N. $0^\circ 57' 00''$ W., beginning new measurement.

Continue over SE. slope.

2.90 Spur, slopes NE.; desc. over broken N. slope.

17.400 The center N 1/16 sec. cor. of sec. 7, established by N. E.
Richardson, Registered Land Surveyor No. 35, in 1947, and is
accepted as the corner, monumented with an iron pipe, 3/4 in.
diam., firmly set, flush with the ground, from which the remains
of bearing trees mkd. by Richardson:

A fir stump, 24 ins. diam., bears S. 51° E., 66 lks.
dist., with scribe marks 1/16 S7 CS visible on
rotted blaze.

A rotted fir stump, 20 ins. diam., bears N. $83\ 1/4^\circ$ W.,
45 lks. dist., no marks remaining.

The corner is located at the corner of fences, bearing N., S.,
and E.

N. $0^\circ 57' 00''$ W., beginning new measurement.

Continue over N. slope.

5.55 Asphalt road, 30 lks. wide, bears N. 80° W. and S. 80° E.

17.400 The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented with an iron post, 1
in. diam., firmly set, projecting 12 ins. above ground, with
brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 6}{S\ 7}$
1924

from which a bearing tree mkd. by Glen L. Baughman, Registered
Land Surveyor No. 536, in 1973

An ash, 6 ins. diam., bears S. $1\frac{1}{4}^\circ$ W., 280 lks. dist.,
with scribe marks $\frac{1}{4}$ S BT visible on partially healed blaze.

and a new bearing tree

A Scotch pine, 6 ins. diam., bears S. $10\frac{1}{2}^\circ$ E.,
158 lks. dist., mkd. $\frac{1}{4}$ S7 BT.