

County Surveyor's Record, Douglas County, Oregon

18511

Subdivision of Section 7,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>The corner is located in a Christmas tree farm with no suitable trees available within limits in sec. 6</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, the top 8 ins. below the ground surface, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 7 S 8 1924 </p> <p>from which the remains of a bearing tree mkd. by N. E. Richardson, Registered Land Surveyor No. 35, in 1947</p> <p style="padding-left: 40px;">An oak stump, 26 ins. diam., bears S. $14\frac{1}{4}^\circ$ W., 174 lks. dist., with scribe marks $\frac{1}{4}$ S visible on opened blaze.</p> <p>and a reference monument, established by James W. Byron, Deputy County Surveyor, in 1962</p> <p style="padding-left: 40px;">An iron rod, $\frac{3}{4}$ in. diam., firmly set, projecting 4 ins. above ground, bears S. $1^\circ 28'$ E., 36 lks. dist.</p> <p>The corner is located in an open pasture, 36 lks. N. of an E. and W. fence line, with no suitable trees available within limits.</p> <p>N. $82^\circ 46' 00''$ W., on the E. and W. center line of sec. 7.</p> <p>Ascend over broken E. slope, through open pasture land.</p>
12.70	Gravel road, 25 lks. wide, bears N. 20° E. and S. 20° W.; enter heavy timber and dense undergrowth.
20.300	<p>The center E $\frac{1}{16}$ sec. cor. of sec. 7, established by N. E. Richardson, Registered Land Surveyor No. 35, in 1947, and is accepted as the corner; monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, projecting 3 ins. above ground, from which a bearing object recorded by Richardson:</p> <p style="padding-left: 40px;">The NE. corner of a house porch, bears N. $22\frac{1}{2}^\circ$ W., 0.22 chs. dist.</p> <p style="text-align: center;">_____</p> <p>N. $82^\circ 46' 00''$ W., beginning new measurement.</p> <p>Continue over broken E. slope.</p>
20.300	<p>The center $\frac{1}{4}$ sec. cor. of sec. 7.</p> <p style="text-align: center;">_____</p> <p>N. $82^\circ 46' 00''$ W., beginning new measurement.</p> <p>Continue over broken E. slope.</p>
4.40	Spur, slopes N. 35° E.; desc. over broken NW. slope.
13.50	Ravine, drains N. 20° W.; asc. over broken NE. slope.
20.70	Spur, slopes N.; desc. over NW. slope.
21.340	<p>Point for the center W $\frac{1}{16}$ sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> W $\frac{1}{16}$ C S 7 C 1988 </p>