

County Surveyor's Record, Douglas County, Oregon

18512

Subdivision of Section 7,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 78° E., 38 lks. dist., mkd. CW 1/16 S7 BT.</p> <p style="margin-left: 40px;">A white fir, 16 ins. diam., bears N. 61° W., 14 lks. dist., mkd. CW 1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, a point established as the center W 1/16 sec. cor. by Burton W. Holt, Registered Land Surveyor No. 418, in 1979, bears N. 82° 51' W., 0.724 chs. dist., monumented with a steel rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, from which bearing trees mkd. by Holt:</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears S. 53° W., 20 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears N. 30° W., 13 lks. dist., with healed blaze.</p> <p>Point is not accepted, as Holt set it at midpoint rather than proportionate position.</p> <p>Continue over broken NW. slope.</p>
28.29	A point established by William S. Barnes, Registered Engineer No. 2128, in 1976, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground.
34.50	Ravine, drains N. 15° W.; asc. over NE. slope.
38.21	A point established by William S. Barnes, Registered Engineer No. 2128, in 1976, monumented with an iron bolt, 5/8 in. diam., loosely set, projecting 12 ins. above ground.
42.30	Spur, slopes N.; desc. over NW. slope.
44.120	The 1/4 sec. cor. of sec. 7 only, on the W. bdy. of the Tp.
	<p>From the W 1/16 sec. cor. of secs. 7 and 18.</p> <p>N. 0° 36' 00" E., on the N. and S. center line of the SW 1/4 of sec. 7.</p> <p>Ascend over steep SE. slope, through heavy timber and dense undergrowth.</p>
6.10	Ridge, bears N. 60° W. and S. 60° E.; along E. slope.
16.80	Spur, slopes NE.; desc. over NW. slope.
20.690	<p>Point for the SW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the SW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, supported in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	<p>SW 1/16 S 7 1988</p>