

County Surveyor's Record, Douglas County, Oregon

18513

Subdivision of Section 7,
T. 29 S., R.7 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 85° E., 5 lks. dist., mkd. SW 1/16 S7 BT.</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 13° W., 20 lks. dist., mkd. SW 1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, a point established as the SW 1/16 sec. cor., and not accepted in this survey, by Burton W. Holt, Registered Land Surveyor No. 418, in 1979, bears N. 80° 28' W., 0.362 chs. dist., monumented with a steel rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Holt:</p> <p style="margin-left: 40px;">A fir, 25 ins. diam., bears N. 65° E., 18½ lks. dist., with bark scribes SE LOT 15 S7 BT visible.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 57° W., 8 lks. dist., with healed blaze.</p> <p>Continue over broken NW. slope.</p>
41.370	<p>The center W 1/16 sec. cor. of sec. 7.</p>
0.80	<p>From the center S 1/16 sec. cor. of sec. 7.</p> <p>N. 79° 24' 00" W., on the E. and W. center line of the SW¼ of sec. 7.</p> <p>Ascend over NE. slope, through heavy timber and dense undergrowth.</p>
6.60	<p>Spur, slopes N. 25° E.; desc. over NW. slope.</p>
20.30	<p>Creek, 3 lks. wide, course N. 50° E.; asc. over broken E. slope.</p>
22.090	<p>Spur, slopes NE.; desc. over NW. slope.</p>
44.850	<p>The SW 1/16 sec. cor. of sec. 7.</p> <p>Continue over broken NW. slope.</p> <p>The S 1/16 sec. cor. of sec. 7 only, on the W. bdy. of the Tp.</p>
<p>Subdivision of Section 19, T. 29 S., R. 7 W., Willamette Meridian, Oregon</p>	
9.515	<p>From the ¼ sec. cor. of secs. 19 and 30.</p> <p>N. 2° 24' 30" E., on the N. and S. center line of sec. 19.</p> <p>Ascend over broken SW. slope, through heavy timber and moderate undergrowth.</p> <p>Point for the center S-S 1/64 sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
<p>S 19 C-S-S 1/64 1988</p>	