

County Surveyor's Record, Douglas County, Oregon

18517

Subdivision of Section 19,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

From the center E-E 1/64 sec. cor. of sec. 19.

N. 1° 34' 00" E., on the N. and S. center line of the SE $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 19.

Ascend over broken SE. slope, through heavy timber and moderate undergrowth.

9.340 Point for the SE-NE 1/64 sec. cor. of sec. 19, at calculated position.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

SE NE 1/64
S 19
1988

from which

A fir, 13 ins. diam., bears S. 20° E., 50 lks. dist.,
mkd. SE NE 1/64 S19 BT.

A fir, 24 ins. diam., bears N. 46 $\frac{1}{2}$ ° W., 41 lks. dist.,
mkd. X BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From the S-N 1/64 sec. cor. of secs. 19 and 20.

N. 82° 43' 30" W., on the E. and W. center line of the SE $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 19.

Ascend over broken SE. slope, through heavy timber and moderate undergrowth.

9.755 The SE-NE 1/64 sec. cor. of sec. 19.

From the E 1/16 sec. cor. of secs. 19 and 30.

N. 1° 15' 00" E., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 19.

Descend over broken NW. slope, through heavy timber and moderate undergrowth.

14.80 Gravel road, 20 lks. wide, bears N. 40° E. and S. 40° W.

19.115 Point for the SE 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the SE $\frac{1}{4}$.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SE 1/16 S 19
1988

from which

A fir, 11 ins. diam., bears S. 70° W., 27 lks. dist.,
mkd. SE 1/16 S19 BT.

A fir, 15 ins. diam., bears N. 54° W., 27 lks. dist.,
mkd. X BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.