

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 19,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

18550

CHAINS	
	Ascend over SW. slope.
19.050	Point for the SW 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the SW $\frac{1}{4}$. Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. SW 1/16 S 19 1988 from which A fir, 17 ins. diam., bears S. 38 $\frac{1}{4}$ ° E., 49 $\frac{1}{2}$ lks. dist., mkd. SW 1/16 S19 BT. A fir, 18 ins. diam., bears S. 83° W., 33 lks. dist., mkd. X BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
29.50	Gravel road, 20 lks. wide, bears N. 40° E. and S. 50° W.
38.135	The center W 1/16 sec. cor. of sec. 19.
	From the center S 1/16 sec. cor. of sec. 19. N. 80° 32' 30" W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 19. Ascend over broken SE. slope, through heavy timber and moderate undergrowth.
20.770	The SW 1/16 sec. cor. of sec. 19.
31.80	Spur, slopes S. 25° W.; desc. over NW. slope.
42.275	The S 1/16 sec. cor. of sec. 19 only, on the W. bdy. of the Tp.
	From the center S-S 1/64 sec. cor. of sec. 19. N. 80° 30' 30" W., on th E. and W. center line of the SE $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 19. Ascend over brokwn SE. slope, through heavy timber and moderate undergrowth.
20.570	The center S-SW 1/64 sec. cor. of sec. 19.
	Survey for the Location of the Oro Grande Placer Claim in Section 19, T. 29 S., R. 7 W., Willamette Meridian, Oregon.
	From Cor. No. 1 (east center end corner) of the Oro Grande placer claim, determined on the line bet. secs. 19 and 20, as indicated in the 1916 Location Notice for the V. Van Gundy placer claim, at a point 0.55 chs. southerly of the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, based on the record call to Coarse Gold Creek by Fred Mensch in 1924. No permanent monument established. S. 0° 07' 30" W., on line 1-2 of Oro Grande placer claim, identical with a portion of the line bet. secs. 19 and 20. Over nearly level bottom land, through medium timber and moderate undergrowth.
0.60	Coarse Gold Creek, 10 lks. wide, course N. 35° E.; asc. over NE. slope.