

County Surveyor's Record, Douglas County, Oregon


Survey for the Location of the Oro Grande Placer Claim in **18552**
 Section 19, T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Ascend over broken SE. slope.

4.545 Point for Cor. No. 5 of the Oro Grande placer claim, determined at a point 300 ft. northerly of Coarse Gold Creek, and 1500 ft. southwesterly of Cor. No. 6.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.



from which

A fir, 10 ins. diam., bears N. 62° E., 28½ lks. dist., mkd. OG 5 BT.

A fir, 14 ins. diam., bears S. 88° W., 36½ lks. dist., mkd. X BT.


N. 60° 02' 00" E., on line 5-6 of Oro Grande placer claim.

Descend over broken SE. slope, through heavy timber and moderate undergrowth.

16.500 Intersect the E. and W. center line of sec. 19.

22.725 Point for Cor. No. 6 of the Oro Grande placer claim, on the line bet. secs. 19 and 20.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.



from which

A fir, 7 ins. diam., bears S. 44° W., 32½ lks. dist., mkd. OG 6 BT.

A fir, 20 ins. diam., bears N. 22° W., 22½ lks. dist., mkd. X BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

S. 1° 17' 00" W., on line 6-1 of Oro Grande placer claim, identical with a portion of the line bet. secs. 19 and 20.

Descend over broken SE. slope, through heavy timber and moderate undergrowth.

3.995 The ¼ sec. cor. of secs. 19 and 20.

S. 0° 07' 30" W., beginning new measurement.

0.550 Corner No. 1 (east center end corner) of the Oro Grande placer claim.