

County Surveyor's Record, Douglas County, Oregon

18561

Corrective Dependent Resurvey of a Portion of the West Boundary,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>The corner is located on a steep, rocky, live oak covered SE. slope.</p>
	<p>N. 0° 22' 00" ^{E PER BLM 2/1/72} W., bet. secs. 13 and 18.</p>
	<p>Ascend over steep, rocky SE. slope, through medium timber and dense undergrowth.</p>
10.40	<p>Spur, slopes S. 70° E.; continue over SE. slope.</p>
19.890	<p>Point for the S 1/16 sec. cor. of secs. 13 and 18.</p>
	<p>From this point, the S 1/16 sec. cor. of secs. 13 and 18, erroneously corrected by Lynn M. Roseberry in 1979, bears N. 15° 52' 00" E., 0.750 chs. dist., set, marked, and witnessed as described in the official record. Remove the iron post, destroy the marks on Roseberry's SW. bearing tree, and at the true corner point</p>
	<p>Reset the iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 1/16 S 13 S 18 1976 1979 1989</p>
	<p>from which a bearing tree mkd. by Popken and Carlson and redescribed by Roseberry</p>
	<p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 40½° E., 86 lks. dist., with healed blaze.</p>
	<p>and a new bearing tree</p>
	<p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 8¼° W., 30 lks. dist., mkd. S 1/16 S13 BT.</p>
	<p>Ascend over steep SE. slope.</p>
32.30	<p>Rocky ridge dividing Cow Creek and Middle Creek drainages, bears N. 60° E., and S. 40° W.; also enter heavy timber and moderate undergrowth, edge bears same; desc. over steep NW. slope.</p>
39.780	<p>Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>From this point, the ¼ sec. cor. of secs. 13 and 18, erroneously corrected by Lynn M. Roseberry in 1979, bears N. 16° 33' 30" E., 0.485 chs. dist., set, marked, and witnessed as described in the official record. Remove the iron post, and at the true corner point</p>
	<p>Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 32 S ¼ R 7 W R 6 W S 13 S 18 1976 1979 1989</p>
	<p>from which bearing trees mkd. by Popken and Carlson, and redescribed by Roseberry</p>
	<p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 35° E., 47 lks. dist., with healed blaze.</p>
	<p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 75 3/4° W., 30½ lks. dist., with healed blaze.</p>