

County Surveyor's Record, Douglas County, Oregon

18563

Dependent Resurvey of a Portion of the North Boundary,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 44 ins. diam., bears N. 54° W., 47 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by the County Surveyor's Office</p> <p>A fir, 28 ins. diam., bears N. 43° E., 46 lks. dist., with healed blaze.</p> <p>A fir, 19 ins. diam., bears S. 25° W., 27 lks. dist., with healed blaze.</p> <p>A fir, 17 ins. diam., bears N. 28° W., 36 lks. dist., with healed blaze.</p> <p>No suitable tree available in sec. 2.</p> <p>N. 89° 25' 30" W., bet. secs. 3 and 34.</p> <p>Across a broken N. slope, along N. edge of timber.</p>
7.00	Spur, slopes N.
19.925	<p>The E 1/16 sec. cor. of secs. 3 and 34, established and recorded by Ronald A. Quimby, Registered Land Surveyor No. 1654, in 1980, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 34}{S\ 3}$</p> <p>from which bearing trees mkd. by Quimby</p> <p>A madrone, 7 ins. diam., bears S. 16° E., 21 lks. dist., with scribe marks E 1/16 S3 BT visible on the bark.</p> <p>A high stumped fir, 22 ins. diam., bears N. 16° W., 61 lks. dist., with scribe marks E 1/16 S34 visible on an open and burned blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 22' 30" W., beginning new measurement.</p>
0.50	Spur, slopes N., also NW. cor. of timber, edge bears S. and E.; desc. open NW. slope.
7.40	Ravine, drains N., also SE. cor. of timber, edge bears N. and W.; asc. NE. slope along S. edge of timber.
16.00	Enter timber, edge bears S. and E.
19.915	<p>The 1/4 sec. cor. of secs. 3 and 34, reestablished by proportionate measurement and recorded by Ronald A. Quimby, Registered Land Surveyor No. 1654, in 1980. There is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd. 1/4 S34 S3 and a horizontal line, from which bearing trees mkd. by Quimby:</p> <p>A fir, 15 ins. diam., bears N. 22° E., 12 lks. dist., with illegible scribe marks visible on a partially healed blaze.</p> <p>A fir, 12 ins. diam., bears S. 60° E., 30 lks. dist., with illegible scribe marks visible on a partially healed blaze.</p> <p>At the corner point</p>