

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the North Boundary, **18561**
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 S R 6 W $\frac{1}{4} \frac{S 34}{S 3}$ T 32 S 1986</p> <p>Deposit the iron rod inside and a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on steep N. slope in timber.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 30' 00" W., beginning new measurement.</p> <p>Ascend along a broken N. slope, through heavy timber and underbrush.</p>
7.50	Gravel road, 25 lks. wide, bears N. 60° W. and S. 60° E.
8.50	Spur, slopes N. 25° E.; desc. NW. slope.
10.60	Gravel road, 25 lks. wide, bears N. 60° E. and S. 60° W.
12.80	Same road, bears N. 60° E. and S. 60° W.
13.30	Ravine, drains N. 15° E.; asc. NE. slope.
14.00	Junction of gravel roads, 25 lks. wide, bears N. 30° W., S. 75° E. and S. 45° E.
19.925	<p>The W 1/16 sec. cor. of secs. 3 and 34, established and recorded by Ronald A. Quimby, Registered Land Surveyor No. 1654, in 1980, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set in a down fir log, 30 ins. diam., with aluminum cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S 34}{S 3}$</p> <p>from which bearing trees mkd. by Quimby</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. 47° E., 50 lks. dist., with illegible scribe marks visible on a partially healed blaze.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 36¼° W., 15½ lks. dist., with illegible scribe marks visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 29' 30" W., beginning new measurement.</p> <p>Continue ascending along N. slope.</p>
5.70	Spur, slopes S. 10° E., desc. NW. slope.
13.90	Ravine, drains N. 15° E.; asc. NE. slope.
19.920	<p>The cor. of secs. 3, 4, 33, and 34, perpetuated by Romano E. Ware, Registered Land Surveyor No. 1005, in 1980, and recorded by Ronald A. Quimby, Registered Land Surveyor No. 1654, in 1980; monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 S R 6 W $\frac{S 33 S 34}{S 4 S 3}$ T 32 S 1980 RLS 1005</p>