

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of a Portion of
the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

18566

CHAINS															
20.050	<p>Point for the W 1/16 sec. cor. of secs. 10 and 15.</p> <p>From this point, the W 1/16 sec. cor. of secs. 10 and 15, erroneously established by Aanrud, in 1966-67, bears N. 1° 38' 30" W., 0.230 chs. dist., set, mkd., and witnessed as described in the official record. Remove the iron post and at the true corner point</p> <p>Reset the iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">W 1/16</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 10</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">S 15</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">1986</td> </tr> </table> </div> <p>from which bearing trees mkd. by Aanrud</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 1 3/4° E., 50 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 46 3/4° W., 16 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 58° E., 20 lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of iron post.</p>	W 1/16	S 10		S 15		1986								
W 1/16	S 10														
	S 15														
	1986														
21.00	Creek, 2 lks. wide, course S. 10° W.; asc. along SE. slope.														
24.80	Spur, slopes S.; desc. along SW. slope.														
40.100	<p>The cor. of secs. 9, 10, 15, 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">T 32 S</td> <td style="padding-right: 10px;">R 6 W</td> </tr> <tr> <td style="border-left: 1px solid black; padding-left: 10px;">S 9</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 10</td> </tr> <tr> <td style="border-left: 1px solid black; padding-left: 10px;">S 16</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 15</td> </tr> <tr> <td></td> <td style="padding-left: 10px;">1966</td> </tr> </table> </div> <p>from which bearing trees mkd. by Aanrud</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 15° E., 47 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A yellow pine, 13 ins. diam., bears S. 54° E., 18 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A chinkapin snag, 7 ins. diam., bears S. 46° W., 31 lks. dist., with scribe marks T32S R6W S16 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 33° W., 43 lks. dist., with healed blaze.</p> <p>No suitable tree available in sec. 16.</p> <p>From this point, a point established by person(s) unknown, bears N. 74° 40' 30" E., 0.875 chs. dist., monumented with an iron pipe 1 in. diam., firmly set, projecting 21 ins. above ground.</p> <p>From this same point, the ¼ sec. cor. of secs. 9 and 16, bears N. 89° 24' 30" W., 39.565 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">T 32 S</td> <td style="padding-right: 10px;">R 6 W</td> </tr> <tr> <td style="border-left: 1px solid black; padding-left: 10px;">¼ S 9</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 16</td> </tr> <tr> <td></td> <td style="padding-left: 10px;">1966</td> </tr> </table> </div>	T 32 S	R 6 W	S 9	S 10	S 16	S 15		1966	T 32 S	R 6 W	¼ S 9	S 16		1966
T 32 S	R 6 W														
S 9	S 10														
S 16	S 15														
	1966														
T 32 S	R 6 W														
¼ S 9	S 16														
	1966														