

County Surveyor's Record, Douglas County, Oregon

18567

Corrective Dependent Resurvey of a Portion of
the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A sawed sugar pine stump, 48 ins. diam., bears N. 8° E., 52 lks. dist., with a partially exposed face, no marks visible.

A root hole, bears S. 5° E., 26 lks. dist., with a down fir, 32 ins. diam., alongside, no marks visible.

and bearing trees mkd. by Aanrud

A cedar, 20 ins. diam., bears S. 69 3/4° E., 15 lks. dist., with illegible scribe marks visible on a partially healed blaze. (Record, S. 61° E.)

A fir, 20 ins. diam., bears N. 84 1/2° W., 49 lks. dist., with healed blaze. (Record, N. 83° W.)

and a bearing tree mkd. by person(s) unknown

A cedar, 24 ins. diam., bears S. 36 1/2° W., 20 1/2 lks. dist., with healed blaze and illegible cruiser mark.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars, in 1881,
and the resurveys by Rollin D. Aanrud, in 1966-67 and 1980)

From the 1/4 sec. cor. of secs. 14 and 23, perpetuated by person(s) unknown, further perpetuated and recorded by Ronald A. Brandt, Registered Land Surveyor No. 841, in 1978, monumented with an iron rod, 1 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of the original bearing tree:

A rotted fir stump, 36 ins. diam., bears S. 1° W., 24 lks. dist., with scribe marks 1/4 BT visible on a loose piece of overgrowth lying on the stump.

and bearing trees mkd. by Brandt

A bigleaf maple, 11 ins. diam., bears N. 29° E., 45 1/2 lks. dist., with scribe marks 1/4 S14 PS841 BT visible on a partially healed blaze.

A tanoak, 9 ins. diam., bears S. 3 1/4° E., 66 1/2 lks. dist., with scribe marks 1/4 3 visible on a partially healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 32 S R 6 W
1/4 S 14
 S 23
 1986

from which a new bearing tree

A fir, 13 ins. diam., bears S. 15° W., 114 1/2 lks. dist., mkd. 1/4 S23 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.