

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, **18568**
T 32 S., R 6 W., Willamette Meridian, Oregon

CHAINS

From this point, the W. end of a woven wire fence, extending generally E., bears S. 71¼° E., 0.30 chs. dist.

S 89° 04' 30" W., bet. secs. 14 and 23.

Ascend steep E. slope, through timber and heavy undergrowth.

14.00 Top of ascent, slopes S. 10° E.; desc. across SW. slope.

19.705 Point for the W 1/16 sec. cor. of secs. 14 and 23. This point is occupied by an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, unofficially established in 1976 by a Bureau of Land Management administrative survey.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

| | |
|--------|------|
| W 1/16 | S 14 |
| | S 23 |
| | 1986 |

from which

A tanoak, 8 ins. diam., bears S. 51° E., 37 lks. dist., mkd. W 1/16 S23 BT.

A madrone, 18 ins. diam., bears N. 57° W., 24 lks. dist., mkd. W 1/16 S14 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post and the iron rod alongside.

Ascend across S. slope.

25.55 Begin descending SW. slope.

39.410 The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

| | |
|--------|-------|
| T 32 S | R 6 W |
| S 15 | S 14 |
| S 22 | S 23 |
| | 1966 |

from which an original bearing tree

A live oak, 14 ins. diam., bears N. 50° W., 23 lks. dist., no marks visible on open blaze.

and bearing trees mkd. by Aanrud

A fir, 18 ins. diam., bears N. 11 3/4° E., 67 lks. dist., with healed blaze. (Record, N. 9½° E., 69 lks.)

A madrone, 12 ins. diam., bears S. 74° E., 53 lks. dist., with illegible scribe marks visible on a partially healed blaze. (Record, S. 72° E., 57 lks.)

A madrone, 7 ins. diam., bears S. 13 3/4° W., 42 lks. dist., with scribe marks T32S R6W S23 BT visible on a partially healed blaze. (Record, S. 10° W., 43 lks.)

A live oak, 13 ins. diam., bears N. 14¼° W., 22 lks. dist., with scribe marks 32S R6W S15 BT visible on a partially healed blaze. (Record, N. 10° W.)

From the ¼ sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.