

County Surveyor's Record, Douglas County, Oregon

18569

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

T 32 S R 6 W

$\frac{1}{4}$
 S 15 | S 14
 1966

from which bearing trees mkd. by Aanrud

A fir, 18 ins. diam., bears S. 55° E., 70 lks. dist.,
with healed blaze.

A cedar, 22 ins. diam., bears N. 74° W., 26 lks. dist.,
with healed blaze.

and a bearing tree mkd. by person(s) unknown

A fir, 26 ins. diam., bears N. 70 3/4° W., 109 lks. dist.,
with axe marks visible on an opened blaze.

N. 0° 32' 00" W., bet. secs. 14 and 15.

Ascend over a broken SE. slope, through timber and heavy undergrowth.

- 0.10 Creek, 1 lk. wide, course E.
- 4.90 Ravine, drains S. 80° E.
- 6.40 Spur, slopes S. 60° E.
- 12.20 Ravine, drains S. 60° E.
- 19.50 Spur, slopes S. 65° E.
- 39.710 The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

T 32 S R 6 W

S 10 | S 11
 S 15 | S 14
 1966

from which bearing trees mkd. by Lorne VanSwearingen, Registered Professional engineer No. 4186, in 1963

A fir, 25 ins. diam., bears N. 3¼° E., 63 lks. dist.,
with healed blaze. (Record, N. 5° E., 64 lks.)

A madrone, 18 ins. diam., bears S. 16° E., 31 lks. dist.,
with healed blaze. (Record, S. 18° E., 32 lks.)

A fir, 22 ins. diam., bears S. 39° W., 4 lks. dist.,
with healed blaze.

A sugar pine, 14 ins. diam., bears N. 20¼° W., 69 lks. dist.,
with healed blaze. (Record, N. 19° W.)

and bearing trees mkd. by Aanrud

A fir, 15 ins. diam., bears N. 14¼° E., 61 lks. dist.,
with healed blaze. (Record, N. 16° E.)

A sugar pine, 26 ins. diam., bears S. 58° W., 38 lks. dist.,
with healed blaze. (Record, 39 lks.)

From this point, a point established by person(s) unknown, bears N. 35° E., 0.70 chs. dist., monumented with a mound of stone, 3 ft. base, 1 ft. high.