

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon 18570

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set with top projecting 2 ins. above mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W $\frac{1}{4}$ $\frac{S 11}{S 14}$ 1966 1980</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A root hole, bears N. 30° E., 36 lks. dist., with a dead and down fir, 22 ins. diam., alongside, no marks visible.</p> <p style="padding-left: 40px;">A burnt fir snag, 32 ins. diam., bears S. 30° W., 4 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Aanrud</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 54° W., 25 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 8$\frac{1}{4}$° W., 29 lks. dist., with healed blaze. (Record, N. 5° W.)</p> <p>S. 89° 36' 30" W., bet. secs. 11 and 14.</p> <p>Ascend E. slope, along S. edge of timber.</p>
7.00	Northwest cor. of logged area, edge bears E. and S.; enter timber.
15.50	Slope changes to SE.
19.615	From this point, a point established by person(s) unknown, bears South, 1.00 ch. dist., monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 14 ins. above ground.
25.70	Shallow ravine, drains S. 20° E.
40.825	The cor. of secs. 10, 11, 14, and 15.
19.890	<p>N. 2° 24' 00" E., bet. secs. 10 and 11.</p> <p>Descend a N. slope, through scattering timber and dense undergrowth.</p> <p>The S $\frac{1}{16}$ sec. cor. of secs. 10 and 11, established and recorded by Lloyd D. Smith, Registered Land Surveyor No. 1101, in 1983, and is accepted as the corner; monumented with an aluminum post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">STATE OF OREGON S $\frac{1}{16}$ S 10 S 11 1983 DEPARTMENT OF FORESTRY LS 1101</p> <p>from which bearing trees mkd. by Smith</p> <p style="padding-left: 40px;">A madrone, 13 ins. diam., bears N. 67° E., 17 lks. dist., with scribe marks S $\frac{1}{16}$ S11 BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A madrone, 14 ins. diam., bears S. 9° W., 37 lks. dist., with scribe marks S $\frac{1}{16}$ S10 BT visible on a partially healed blaze.</p>