

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines **18572**
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir snag, 14 ins. diam., bears S. 29° E., 92 lks. dist., with illegible scribe marks visible on a partially healed blaze.</p> <p>and a bearing tree mkd. by person(s) unknown.</p> <p>A fir, 38 ins. diam., bears S. 31½° E., 51 lks. dist., with scribe mark B visible on the bark.</p> <p>and reference monuments set by Orrin K. Frederick, Registered Land Surveyor No. 1987, in 1985</p> <p>An iron rod, 5/8 in. diam., firmly set, projectin 4 ins. above ground, with plastic cap mkd. FREDERICK LS 1987, bears N. 19° 19' E., 43½ lks. dist.</p> <p>An iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap mkd. FREDERICK LS 1987, bears N. 30° 08' W., 52 lks. dist.</p> <p>An iron rod, 5/8 in. diam., firmly set with top flush with the ground, with plastic cap mkd. FREDERICK LS 1987, bears S. 84° 06' W., 40 lks. dist.</p> <p>N. 0° 16' 30" W., bet. secs. 2 and 3.</p> <p>Ascend a broken SW. slope, through timber and moderate undergrowth.</p>
0.75	Gravelled road, 30 lks. wide, bears N. 25° E. and S. 25° W.
12.35	Spur, slopes N. 50° W.; desc. NE. slope.
19.700	<p>The S 1/16 sec. cor. of secs. 2 and 3, established and recorded by Orrin K. Frederick, Registered Land Surveyor No. 1987, in 1985, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with an aluminum cap mkd. S 1/16 S3 S2 1985 LS 1987.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 1/16</p> <p>S 3 S 2</p> <p>1986</p> </div> <p>from which bearing trees mkd. by Frederick</p> <p>A hemlock, 11 ins. diam., bears S. 89° E., 37½ lks. dist., with scribe marks S 1/16 S2 LS 1987 BT on a partially healed blaze.</p> <p>A hemlock, 15 ins. diam., bears N. 27 3/4° W., 36 lks. dist., with scribe marks S 1/16 S3 LS 1987 BT on a partially healed blaze.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A fir, 40 ins. diam., bears N. 44½° E., 41 lks. dist., with healed blaze and two horizontal hacks.</p> <p>Deposit the iron rod inside and a white "DEEP-1" magnetic marker at base of stainless steel post.</p>
	<p style="text-align: center;">_____</p> <p>N. 0° 18' 30" W., beginning new measurement.</p> <p>Continue descending NE. slope.</p>