

# County Surveyor's Record, Douglas County, Oregon

1857.3 Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
10.60	West edge of gravelled road, 30 lks. wide, bears N. and S. on a switchback.
16.00	Creek, 2 lks. wide, course N. 60° E.; asc. along E. slope.
19.695	<p>The ¼ sec. cor. of secs. 2 and 3, perpetuated by the Douglas County Surveyor's Office in 1967, and further perpetuated and recorded by Orrin K. Frederick, Registered Land Surveyor No. 1987, in 1985, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 32 S R 6 W ¼ 3 2 1967</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears East, 32 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. 80° W., 17½ lks. dist., with scribe mark B visible on open blaze. (Record, 20 lks.)</p> <p>and a bearing tree mkd. by Frederick</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 15° E., 79 lks. dist., with scribe marks ¼ S2 LS 1987 BT visible on a partially healed blaze.</p>
14.90	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>S. 89° 45' 00" W., bet. secs. 15 and 22.</p> <p>Descend SW. slope, through heavy timber and dense undergrowth.</p> <p>Spur, slopes SW.; desc. NW. slope.</p>
20.875	<p>The E 1/16 sec. cor. of secs. 15 and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16    <math>\frac{S \ 15}{S \ 22}</math> 1966</p> <p>from which bearing trees mkd. by Aanrud</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears N. 13° E., 18 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A chinkapin, 16 ins. diam., bears S. 45° W., 21 lks. dist., with illegible scribe marks visible on a partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 35' 30" W., beginning new measurement.</p>
8.50	Creek, 3 lks. wide, course SW.; asc. SE. slope.
9.70	Spur, slopes S. 30° W.; desc. SW. slope.
14.80	Gravelled road, 30 lks. wide, bears N. and S.
17.50	Wood Creek, 20 lks. wide, course S. 5° W.; asc. E. slope.