

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines **18576**
 T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A cedar, 28 ins. diam., bears S. 37° W., 22 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 47' 00" W., beginning new measurement.</p> <p>Ascend SE. slope, changing to E.</p>
13.40	<p>Spur, slopes N. 40° E.; desc. NE. slope.</p>
19.985	<p>The N 1/16 sec. cor. of secs. 15 and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 16 S 15 1966</p> <p>from which bearing trees mkd. by Aanrud</p> <p style="text-align: center;">A fir, 10 ins. diam., bears S. 12° E., 41 lks. dist., with healed blaze. (Record, 40 lks.)</p> <p style="text-align: center;">A fir, 11 ins. diam., bears N. 2° W., 34 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 57' 00" W., beginning new measurement.</p> <p>Descend NE. slope.</p>
6.55	<p>Ravine, drains N. 20° E.</p>
13.00	<p>Wood Creek, 30 lks. wide, course S. 85° E.; asc. SW. slope.</p>
15.50	<p>Gravelled road, 30 lks. wide, bears NW. and SE.</p>
19.965	<p>The cor. of secs. 9, 10, 15, and 16.</p>
	<p>N. 1° 44' 30" E., bet. secs. 9 and 10.</p> <p>Ascend SW. slope, through scattering timber and dense undergrowth.</p>
1.00	<p>Top of ascent, slopes W.; desc. NW. slope.</p>
11.45	<p>Creek, 8 lks. wide, course S. 30° W.; asc. SE. slope.</p>
13.15	<p>Gravelled road, 30 lks. wide, bears N. 30° E. and S. 30° w.</p>
19.935	<p>The S 1/16 sec. cor. of secs. 9 and 10, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 9 S 10 1967</p> <p>from which bearing trees mkd. by Aanrud</p> <p style="text-align: center;">A chinkapin, 10 ins. diam., bears N. 34° E., 15 lks. dist., with healed blaze.</p> <p style="text-align: center;">A madrone, 6 ins. diam., bears S. 65° W., 13½ lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: auto;"/>