

County Surveyor's Record, Douglas County, Oregon

18577

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	<p>N. 1° 40' 00" E., beginning new measurement.</p> <p>Ascend SE. slope, through heavy timber.</p>
19.895	<p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W $\frac{1}{4}$ S 9 S 10 1966</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A root hole, bears N. 50° E., 3 lks. dist., with the rotted remains of a dead and down cedar, size indeterminate, alongside, no marks visible.</p> <p style="padding-left: 40px;">A root hole, bears N. 80° W., 23 lks. dist., with the rotted remains of a madrone, size indeterminate, alongside, no marks visible.</p> <p>and bearing trees mkd. by Aanrud</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 63½° E., 46 lks. dist., with healed blaze. (Record, S. 61° E.)</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 33° W., 36 lks. dist., with healed blaze.</p>
<p>Corrective Dependent Resurvey of the Northwest Quarter of Section 15, T. 32 S., R. 6 W., Willamette Meridian, Oregon</p>	
<p>(Correcting the survey by Rollin D. Aanrud in 1966)</p>	
20.020	<p>From the center W 1/16 sec. cor. of sec. 15, hereinafter described.</p> <p>N. 0° 33' 30" W., on the N. and S. center line of the NW¼ of sec. 15.</p> <p>Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the NW¼.</p> <p>From this point, the NW 1/16 sec. cor. of sec. 15, erroneously established by Rollin D. Aanrud in 1966, bears N. 89° 35' 30" W., 0.050 chs. dist., set, marked, and witnessed as described in the official record. Remove the iron post and at the true corner point</p> <p>Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 15 1966 1989</p> <p>from which bearing trees mkd. by Aanrud</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 7° W., 73 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 48¼° W., 20½ lks. dist., with healed blaze.</p>
40.110	<p>The W 1/16 sec. cor. of secs. 10 and 15.</p>