

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of the Northwest Quarter of
 Section 15, T. 32 S., R. 6 W., Willamette Meridian, Oregon 18578

CHAINS	
	<p>From the center N 1/16 sec. cor. of sec. 15, hereinafter described.</p> <p>S. 89° 23' 30" W., on the E. and W. center line of the NW¼ of sec. 15.</p>
19.840	The NW 1/16 sec. cor. of sec. 15.
39.740	The N 1/16 sec. cor. of secs. 15 and 16.
<p>Dependent Resurvey of a Portion of the Subdivision of Section Lines of Section 15, T. 32 S., R. 6 W., Willamette Meridian, Oregon</p>	
<p>(Restoring the survey by Rollin D. Aanrud in 1966-67)</p>	
	<p style="text-align: center;">From the ¼ sec. cor. of secs. 15 and 22.</p> <p>N. 0° 07' 00" W., on the N. and S. center line of sec. 15.</p>
9.850	<p>The center S 1/16 sec. cor. of sec. 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C S 1/16 S 15 C 1966</p> </div> <p>from which bearing trees mkd. by Aanrud</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears N. 67¼° E., 20 lks. dist., with healed blaze. (Record N. 73° E.)</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears S. 60° W., 36 lks. dist., with healed blaze.</p>
	<p style="text-align: center;">N. 0° 01' 30" W., beginning new measurement.</p>
19.875	<p>The center ¼ sec. cor. of sec. 15, monumented with an iron post, firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C¼ S 15 1966</p> </div> <p>from which bearing trees mkd. by Aanrud</p> <p style="margin-left: 40px;">A cedar, 16 ins. diam., bears S. 6° E., 20 lks. dist., with scribe marks C¼ S15 BT visible on a partially healed blaze.</p> <p style="margin-left: 40px;">A cedar, 18 ins. diam., bears N. 55° W., 6 lks. dist., with scribe marks ¼ S15 BT visible on a partially healed blaze.</p>
	<p style="text-align: center;">N. 0° 29' 30" W., beginning new measurement.</p>
20.055	<p>The center N 1/16 sec. cor. of sec. 15, monumented with an iron post, firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C N 1/16 S 15 C 1966</p> </div>