

# County Surveyor's Record, Douglas County, Oregon

## 18579

Dependent Resurvey of a Portion of the Subdivision  
of Section Lines of Section 15,  
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
20.205	<p>from which bearing trees mkd. by Aanrud</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 69° E., 47 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 57° W., 27 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' 00" E., beginning new measurement.</p> <p>The ¼ sec. cor. of secs. 10 and 15.</p>
19.825	<p>From the center ¼ sec. cor. of sec. 15.</p> <p>S. 89° 33' 30" W., on the E. and W. center line of sec. 15.</p> <p>The center W 1/16 sec. cor. of sec. 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{ccc} &amp; \text{W } 1/16 &amp; \\ \text{C} &amp; \text{S } 15 &amp; \text{C} \\ &amp; 1966 &amp; \end{array}</math> </div> <p>from which the remains of the bearing trees mkd. by Aanrud</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 53° E., 21 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A rotted fir stump, 17 ins. diam., bears N. 21° W., 21 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 37° W., 11 lks. dist., mkd. CW 1/16 S15 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 34' 30" W., beginning new measurement.</p> <p>The ¼ sec. cor. of secs. 15 and 16</p>
<p>Subdivision of Section 15, T. 32 S., R. 6 W., Willamette Meridian, Oregon</p>	
19.910	<p>From the W 1/16 sec. cor. of secs. 15 and 22.</p> <p>N. 0° 37' 00" W., on the N. and S. center line of the SW¼ of sec. 15.</p> <p>Descend E. slope, through heavy timber and undergrowth.</p> <p style="padding-left: 40px;">Ravine, drains N. 60° E.; desc. broken NE. slope.</p> <p>Point for the SW 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the SW¼.</p> <p>Set a stainless steel post, 28 ins. long 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{ccc} \text{SW } 1/16 &amp; \text{S } 15 &amp; \\ &amp; 1986 &amp; \end{array}</math> </div> <p>from which</p>
8.30	